



technical data

Supply voltage	380 - 415 V 2N/3N
Supply voltage	220 - 240 V
Frequency	50/60 Hz
Maximum power consumption	7.6 kW
Fuse protection / power supply	3 x 16 A
Fuse protection / power supply	2 x 16 A
Fuse protection / power supply	1 x 32 A
Dimensions (WxDxH)	760 x 515 x 199 mm
Surface material	SCHOTT CERAN®
Service life	Max. 150 h / 1 year
Power levels	1 - 9, P
Back cooking zone dimensions	Ø 175 mm
Front cooking zone dimensions	Ø 210 mm
Front cooking zone power	2300 W
Back cooking zone power	1400 W
Front cooking zone power setting	3000 W
Back cooking zone power setting	2100 W
Filter medium	Activated charcoal filter with ion exchanger
Material	Filter panel with fine filter

Product description

- Intuitive sControl control
- eSwap
- effective odour removal
- Minimum volume
- Simple cleaning
- Integrated grease drip pan
- Oversized 4 24 cooking surface
- Maximum storage space
- Automatic extractor control
- Demo mode

Scope of delivery

- Induction cooktop with integrated cooktop extractor - recirculation PURU
- air inlet nozzle
- stainless steel grease filter
- activated charcoal filter
- operating and installation instructions
- drilling template
- Mounting clamps
- sealing tape
- height adjustment plate set
- Housing cover power supply
- Installation accessories for the power supply
- Glass ceramic scraper

Accessories

- Activated charcoal filter PUAKE
- Stainless steel grease filter PUEF
- Air inlet nozzle black PUEB
- Air inlet nozzle pink gold PUEG
- Air inlet nozzle red PUEC
- Air inlet nozzle jade green PUEJ
- Air inlet nozzle orange PUEO
- Air inlet nozzle blue PUEB
- UDB25 sealing tape
- BKR760 cooktop frame
- Air purification box telescopic pull-out PULBTA

product- and planning instructions

- The connection cable must be provided at the installation site
- Front power socket
- Telescopic extension (extension up to 80 mm) of the air purification box for the connection to the body back wall
- The telescopic extension of the air purification box in extra-deep cooktop base cabinets can be extended by 105 mm with an additional telescopic extension PULBTA (available as accessory)
- Ensure sufficient ventilation of the area below the cooktop.
- Installation type: flush or surface-mounted
- The drawers and/or shelves in the floor unit must be removable for maintenance and cleaning purposes
- Please note that induction-compatible cookware must be used on induction cooktops
- The PURE cooktop extractor system can be combined with all BORA sockets
- Not compatible with BORA universal extractors